




API THREADED ADAPTERS

PARVEEN API Threaded Adapters have an API pin thread down and a quick box connection up. These adapters are used for lower working pressures. Any combination of end connections are available on request.

API THREADED ADAPTERS				
Service	I.D. (inch)	W.P. (PSI)	Bottom Conn.	Part No.
STD	2.44	5,000	2-7/8" EU 8 rd	134-035031
H2S	2.44	5,000	2-7/8" EU 8 rd	134-035030
STD	2.50	5,000	3-1/2" EU 8 rd	134-045041
H2S	2.50	5,000	3-1/2" EU 8 rd	134-045040
STD	2.99	5,000	3-1/2" EU 8 rd	134-055041
H2S	2.99	5,000	3-1/2" EU 8 rd	134-055040
H2S	3.95	5,000	4-1/2" EU 8 rd	134-075060
STD	3.59	5,000	4-1/2" EU 8 rd	134-075061
H2S	4.00	5,000	4-1/2"-8 rd long casing	134-085070
STD	4.00	5,000	4-1/2"-8 rd long casing	134-085071
H2S	4.00	5,000	5-1/2"-8 rd long casing	134-085080
STD	4.89	5,000	5-1/2"-8 rd long casing	134-105081
STD	5.00	3,000	7"-8 rd long casing	134-113091
STD	5.00	5,000	7-5/8"-8 rd long casing	134-115101
H2S	5.00	3,000	7"-8 rd long casing	134-113090
H2S	5.00	5,000	7-5/8"-8 rd long casing	134-115100
STD	5.00	5,000	9-5/8"-8 rd long casing	134-115111
H2S	5.00	5,000	9-5/8"-8 rd long casing	134-115110
STD	6.38	5,000	9-5/8"-8 rd long casing	134-135111
H2S	6.38	5,000	9-5/8"-8 rd long casing	134-135110
STD	6.09	3,000	7"-8 rd long casing	134-123091
H2S	6.09	3,000	7"-8 rd long casing	134-123090




**TUBING PIN X
THREADED HALF**

Note: * Other sizes available on request.


* Refer to the Quick Union identification chart on page no. 16 & 17 for end connections.

BLANKING CAPS & PLUGS

PARVEEN Blanking Caps and Plugs are used for installing gauges and / or bleed off valve. These are available for use on all Quick Unions, and are equipped with NPT ports.



BLANKING PLUG



BLANKING CAP