


## PULLING TOOL ('R' SERIES)



**R PULLING  
TOOL**

The PARVEEN 'R' Series Pulling tool is used for jobs in which extensive downward jarring is required. The tool is designed to shear and release by upward jarring. These are available with four different types of cores.

1. RB : Long core, short reach.
2. RS : Medium core, medium reach.
3. RJ : Short core, long reach.
4. RQ : Special core designed to latch a Quick Lock Connection (QLS) connection.

Either of these tools can be changed to other types by changing the core. All other parts remain same.

<b>PULLING TOOL ('R' SERIES)</b>							
<b>Nominal Size (in)</b>	<b>Type</b>	<b>O.D. (in)</b>	<b>F/N O.D. (in)</b>	<b>Pulls Neck O.D. (in)</b>	<b>Top Conn.</b>	<b>Reach (in)</b>	<b>Part No.</b>
1-1/4	RB	1.220	1.000	1.000	5/8 - 11 UNC	1.219	127RB10
1-1/4	RS	1.220	1.000	1.000	5/8 - 11 UNC	2.125	127RS10
1-1/4	RJ	1.220	1.000	1.000	5/8 - 11 UNC	1.844	127RJ4
1-1/2	RB	1.430	1.188	1.188	15/16 - 10 UN	1.265	127RB14
1-1/2	RS	1.430	1.188	1.188	15/16 - 10 UN	1.797	127RS5
1-1/2	RJ	1.430	1.188	1.188	15/16 - 10 UN	2.547	127RJ5
1-1/2	RB	1.484	1.188	1.188	15/16 - 10 UN	1.050	127RB21
1-3/4	RS	1.562	1.188	1.188	15/16 - 10 UN	1.797	127RS14
1-3/4	RJ	1.560	1.188	1.188	15/16 - 10 UN	2.550	127RJ10
2	RB	1.770	1.375	1.375	15/16 - 10 UN	1.219	127RB17
2	RS	1.770	1.375	1.375	15/16 - 10 UN	1.984	127RS6
2	RJ	1.770	1.375	1.375	15/16 - 10 UN	2.547	127RJ1
2-1/2	RB	2.180	1.375	1.750	15/16 - 10 UN	1.203	127RB18
2-1/2	RS	2.180	1.375	1.750	15/16 - 10 UN	1.984	127RS7
2-1/2	RJ	2.180	1.375	1.750	15/16 - 10 UN	2.547	127RJ2
3	RB	2.74	2.312	2.312	1-1/16 - 10 UN	1.297	127RB19
3	RS	2.74	2.312	2.312	1-1/16 - 10 UN	2.190	127RS8
3	RJ	2.74	2.312	2.312	1-1/16 - 10 UN	2.609	127RJ3
3-1/2	RB	3.110	2.312	2.75	1-1/16 - 10 UN	1.350	127RB30
3-1/2	RS	3.110	2.312	2.75	1-1/16 - 10 UN	2.100	127RS16
4	RB	3.670	2.312	3.125	1-1/16 - 10 UN	1.49	127RB20
4	RS	3.718	2.312	3.125	1-1/16 - 10 UN	2.156	127RS9
4	RJ	3.660	2.312	3.125	1-1/16 - 10 UN	2.000	127RJ6