

PARVEEN Self-Releasing Overshot are used to fish wireline tools that have no fishing neck as well as damaged wireline tools and sucker rods that cannot be fished with a magnet.

SELF-RELEASING OVERSHOTS

The tool is operated by applying the weight of the tool string on to the fish, which engages the fish. The harder the operator pulls on the overshot, the tighter the grip of the slips on the tool to be fished becomes. Should it proves impossible to free the jammed tool, a safety device permits the overshot to be released by jarring down. Once the overshot has been recovered, it is possible to change the size of the line to obtain a stronger jarring effect.

SELF-RELEASING OVERSHOTS											
Tubing Size	Body Assembly				Coupling		Skirt		Slips		
O.D. (in)	O.D. (in)	Top Conn.	F/N O.D. (in)	Part No.	Max. O.D. (in)	Part No.	Max. O.D. (in)	Part No.	Fish O.D. (in)		Part No.
2-3/8	1-3/4	15/16-10	1-3/8	M-169413	No Coupling		1-3/4	M-169872	1/2 3/4 1	3/4 1 1-1/4	M-169875 M-169874 M-169873
					1-7/8	M-802877	1-7/8	M-169989	3/4 7/8 1-1/8	1 1-1/8 1-3/8	M-169879 M-169876 M-169878
2-7/8	1-3/4	15/16-10	1-3/8	M-169413	2-1/8	M-803990	2-1/8	M-169880	7/8 1-1/8	1-1/8 1-3/8	M-169884 M-169883
							0.405	14 40000 4	1-3/8 1-1/4	1-5/8 1-1/2	M-169882 M-169643
						Coupling M-803991	2.165 2-1/4	M-169994 M-169991	1-3/8 1-1/2	1-11/16 1-3/4	M-169995 M-169988
3-1/2	2-5/8	1-1/16"	1-3/4	M-169271	No Coupling		2-5/8	M-169885	1-3/8 1-5/8 1-7/8 1-1/4	1-5/8 1-7/8 2-1/8 1-1/2	M-169888 M-169887 M-169886 M-169644
					2-13/16	M-802890	2-13/16	M-169889	1-5/8 1-7/8 2-1/8	1-7/8 2-1/8 2-3/8	M-169893 M-169892 M-169891
4	2-5/8	1-1/16 10 UN	1-3/4	M-169271	3-5/16	M-802895	3-5/16	M-169894	2-1/8 2-3/8 2-5/8	2-3/8 2-5/8 2-7/8	M-169898 M-169897 M-169896

SELF RELEASING OVERSHOT

• Other sizes available on request.