


SINGLE GRIP RETRIEVABLE PACKER MODEL 'R'



**SINGLE GRIP
RETRIEVABLE
PACKER
MODEL 'R'**

PARVEEN Model-R Single-Grip Mechanical Production Packer is a retrievable packer set by compression that isolates the annulus from the production conduit in most production, stimulation, and testing operations. The field-proven design includes rocker slips and a three-element packing system that helps to ensure correct setting and pack off.

Features, Advantages and Benefits:

- The packer parts are interchangeable with equipment from other manufacturers, reducing costs and inventory
- The large bypass enables fluids to equalize quickly and reduces the swabbing effect during run-in and retrieval for faster running
- The standard one-quarter right turn for packer setting provides simple operation on the rig
- A differential lock helps to keep the bypass to the mandrel closed and locked during high-pressure operations to maintain integrity and prevent production loss and the need for a work over to pull out of the hole and redress the packer
- The long-stroke mandrel simplifies fluid circulation without packer release
- The packer automatically returns to the run-in position when moved up the hole to enable circulation through and around it

Options:

- The packer is available with an optional left turn for setting

SINGLE GRIP RETRIEVABLE PACKER MODEL 'R'						
CASING		RECOMMENDED HOLE SIZE (inches)	TOOL OD MAX. (inches)	TOOL ID MIN. (inches)	THREAD CONNECTION BOX UP / PIN DOWN	PART NO.
SIZE (inches)	WEIGHT (lbs/ft)					
4.1/2	9.5-13.5	3.920-4.090	3.771	1.920	2.3/8" EUE	242-3750-XXXX
5	11.5-15	4.408-4.560	4.250	1.920	2.3/8" EUE	242-4250-XXXX
	15-18	4.250-4.408	4.125	1.920	2.3/8" EUE	242-4125-XXXX
5.1/2	20-23	4.625-4.778	4.500	1.930	2.3/8" EUE	242-4625-XXXX
				2.36	2.7/8" EUE	242-4625-XXXX
	15.5-20	4.778-4.950	4.641	1.93	2.3/8" EUE	242-4500-XXXX
				2.36	2.7/8" EUE	242-4500-XXXX
13-15.5	4.950-5.044	4.781	1.93	2.3/8" EUE	242-4781-XXXX	
			2.36	2.7/8" EUE	242-4781-XXXX	
6.5/8	28-32	5.675-5.791	5.490	1.93	2.3/8" EUE	242-5490-XXXX
	24	5.830-5.937	5.656	2.37	2.7/8" EUE	242-5656-XXXX
	17-20	6.456-6.538	5.812	2.37		242-5812-XXXX
7	32-35	6.004-6.094	5.812	2.37	2.7/8" EUE	242-5812-XXXX
	26-29	6.184-6.276	5.968		2.7/8" EUE	242-5968-XXXX
	20-26	6.276-6.456	6.078		2.7/8" EUE	242-6078-XXXX
	17-20	6.456-6.538	6.266			242-6266-XXXX
	33.7-39	6.625-6.765	6.453			242-6453-XXXX
7.5/8	24-29.7	6.875-7.025	6.672	2.37	2.7/8" EUE	242-6672-XXXX
	20-24	7.025-7.125	6.812			242-6812-XXXX
9.5/8	47-53.5	8.535-8.681	8.218	2.97	3.1/2" EUE	242-8218-XXXX
	40-47	8.681-8.835	8.437	2.37	2.7/8" EUE	242-8437-XXXX
				2.97	3.1/2" EUE	242-8437-XXXX

'XXXX' is change as per material / elastomer / end connection